

# DigitalFlow™ GM868

## Panametrics General-Purpose Gas Ultrasonic Flowmeter



### Applications

The DigitalFlow GM868 flow transmitter is a complete ultrasonic flow metering system for measurement of most gases including:

- Hydrocarbon gases
- Vent gases
- Biogases
- Digester gases
- Fuel gases
- Waste gases
- Incinerator air flow
- Vapor recovery
- Stack gases
- Other gases

### Features

- Full-featured flowmeter package
- Transducer removable under line pressure
- No moving parts
- No pressure drop
- Wide rangeability with 1500 to 1 turndown ratio
- Non-obstructive flow measurement
- Tolerance to dirty streams
- Low maintenance
- Suitable for high temperatures
- Two-path measurement available for maximum accuracy



GE imagination at work

## Panametrics Ultrasonic General Purpose Gas Flowmeter

The DigitalFlow GM868 flowmeter uses the patented Correlation Transit-Time™ method of ultrasonic flow measurement to provide accurate, drift-free measurements, without impeding or obstructing the flow.

### Wide Range of Pipe Sizes and Flow Conditions

With its broad range of measurement velocities, and its ability to measure flow in any pipe from small to very large, one DigitalFlow GM868 meter does the job of several conventional meters. It handles pipes from 1 to 120 inches in diameter (2.5 cm to 3 m), and velocities from 0.1 to 150 ft/s (0.03 to 46 m/s)—in either direction, in steady or pulsating flow.

For maximum accuracy, use a two-channel meter to measure along two different paths at the same location. A two-channel meter can also measure the flow in two separate pipes or at two different places in the same pipe.

### No Pressure Drop, Low Maintenance

Since the DigitalFlow GM868's transducers do not obstruct the flow, they generally do not cause any pressure drop as other types of flowmeters do. The DigitalFlow GM868 has no parts that foul or collect debris, and no moving parts to wear out. As a result, it requires no lubrication, cleaning or other routine maintenance.

### Digital and Analog Output Options

The DigitalFlow GM868 flowmeter makes it easy to send the data where it needs to go, through the standard digital output, standard or optional analog outputs or optional alarms. All outputs are conveniently set up and calibrated from the keypad or from a computer using the PanaView program.

Transducer Type	T5 Wetted Transducer				T17 Wetted Transducer			
	Flow Measurement Range							
Standard Range	-150 to 150 ft/s (-50 to 50 m/s) - bidirectional							
	Applicable Pipe Sizes							
Diagonal 45	3 in to 14 in (50 to 350 mm) OD				14 in to 120 in (350 to 3000 mm) OD			
Bias 90	Note 1 & 2				Not Applicable			
	Design Velocity Accuracy from 1 to 150 ft/s (0.3 to 50 m/s)							
Transducer Type	T5 Wetted Transducer				T17 Wetted Transducer			
Number of Paths	One Path		Two Paths		One Path		Two Paths	
	1 ft/s (0.3 m/s)	>3 ft/s (1 m/s)	1 ft/s (0.3 m/s)	>3 ft/s (1 m/s)	1 ft/s (0.3 m/s)	>3 ft/s (1 m/s)	1 ft/s (0.3 m/s)	>3 ft/s (1 m/s)
Pipe Dia. <= 6 in. (150mm)	+2.5%	+2.0%	+2.0%	+1.5%	NA	NA	NA	NA
Pipe Dia. >= 6 in. (150mm)	+2.0%	+2.0%	+1.5%	+1.5%	+2.0%	+2.0%	+1.5%	+1.5%
	Calibrated Velocity Accuracy from 1 to 150 ft/s (0.3 to 50 m/s) — see notes below							
Transducer Type	T5 Wetted Transducer				T17 Wetted Transducer			
Number of Paths	One Path		Two Paths		One Path		Two Paths	
	1 ft/s (0.3 m/s)	>3 ft/s (1 m/s)	1 ft/s (0.3 m/s)	>3 ft/s (1 m/s)	1 ft/s (0.3 m/s)	>3 ft/s (1 m/s)	1 ft/s (0.3 m/s)	>3 ft/s (1 m/s)
Pipe Dia. <= 6 in. (150mm)	+1.5%	+1.0%	+1.0%	+0.75%	NA	NA	NA	NA
Pipe Dia. >= 6 in. (150mm)	+1.0%	+1.0%	+0.75%	+0.75%	+1.0%	+1.0%	+0.75%	+0.75%
	Flow Velocity Sensitivity from .1 to 1 ft/s (0.03 to .3 m/s)							
Pipe Dia. = 10 in. (250mm)	±0.12 in/s(±0.004 m/s)		±0.08 in/s(±0.003 m/s)		NA		NA	
Pipe Dia. = 14 in. (250mm)	±0.12 in/s(±0.004 m/s)		±0.08 in/s(±0.003 m/s)		±0.08 in/s(±0.003 m/s)		±0.06 in/s(±0.002 m/s)	
Pipe Dia. >= 20 in. (500mm)	±0.12 in/s(±0.004 m/s)		±0.08 in/s(±0.003 m/s)		±0.06 in/s(±0.002 m/s)		±0.04 in/s(±0.0015 m/s)	

Note 1 Accuracy and sensitivity are dependent on pipe diameter, molecular weight and temperature. All accuracy specs assume molecular weights greater than 24 kg/kmole and temperatures less than 100 °F (38 °C)

Note 2 Accuracy is dependent on straight run. All accuracy specs assume a fully developed flow profile or a minimum straight run of 20D upstream and 10D downstream

Note 3 Stated accuracy may be achieved with total straight run as little as 10D using flow profile correction - contact factory for details

# GM868 Specifications

## Operation and Performance

### Fluid Types

All acoustically conductive gases

### Pipe Sizes

2 in to 120 in (50 mm to 3,000 mm) NB and larger

### Pipe Materials

All metals. Consult GE for other materials.

### Flow Accuracy (Velocity)

±1% to 2% of reading typical

*Accuracy depends on pipe size and whether measurement is one-path or two-path. Accuracy to ±0.5% of reading may be achievable with process calibration.*

### Repeatability

±0.2% to 0.5% of reading

### Range (Bidirectional)

-150 to 150 ft/s (-46 to 46 m/s)

### Rangeability (Overall)

1500:1

*Specifications assume a fully developed flow profile (typically 20 diameters upstream and 10 diameters downstream of straight pipe run) and flow velocity greater than 3 ft/s (1 m/s).*

### Measurement Parameters

Mass flow, standard and actual volumetric flow, totalized flow, and flow velocity

## Electronics

### Flow Measurement

Transit time

### Enclosures

- Standard: Epoxy-coated aluminum Type 4X/IP66 Class I, Division 1, Groups B,C&D  
Flameproof ISSeP 02ATEX008  
Ⓜ II 2 GD EEx d IIC T5 IP66 T95°C
- Optional: Stainless steel

### Dimensions (h x d)

Standard: Size 8.2 in x 6.6 in (208 mm x 168 mm), weight 10 lb (4.5 kg)

### Channels

- Standard: One channel
- Optional: Two channels (for two pipes or two-path averaging)

### Display

Optional: 2 line x 16 character backlit LCD display, configurable to display up to four measurement parameters in sequence

### Keypad

Built-in infrared, six-button keypad for full functionality operation

### Power Supplies

- Standard: 100-240 VAC
- Optional: 12 to 28 VDC, ±5%

### Power Consumption

20 W maximum

### Operating Temperature

-4° to 131°F (-20° to 55°C)

### Storage Temperature

-67° to 167°F (-55° to 75°C)

### Standard Inputs/Outputs

Two 0/4 to 20 mA isolated outputs, 550 S maximum load  
Namur NE043 compliant

### Optional Inputs/Outputs

There are six additional slots available for any combination of the following I/O boards:

- Analog inputs: Select up to three boards of one of the following types:
  - Analog input board with two isolated 4 to 20 mA inputs and 24V loop power
  - RTD input board with two isolated, three-wire, RTD inputs; span -100° to 350°C (-148° to 662°F); 100 S
- Totalizer/frequency outputs: Select up to three totalizer/frequency output boards, each with four outputs per board, 10 kHz maximum
- Alarm relays: Select up to two boards of one of the following types:
  - General purpose: Relay board with three Form C relays
  - Hermetically sealed: Relay board with three hermetically sealed Form C relays

### Digital Interfaces

- Standard: RS232
- Optional: RS485 (multiuser)
- Optional: Modbus® RS485 or TCP protocol
- Optional: Ethernet
- Optional: OPC server
- Optional: Foundation fieldbus

### Data Logging

- Standard: None
- Optional: Memory capacity (linear and/or circular type) to log over 150,000 flow data points

### European Compliance

System complies with EMC Directive 2004/108/EC, 2006/95/EC LVD (Installation Category II, Pollution Degree 2) and transducers comply with PED 97/23/EC for DN<25

## Wetted Ultrasonic Flow Transducers

### Temperature Range

- Standard: -58°F to 302°F (-50°C to 150°C)
- Optional (overall): -310°F to 842°F (-190°C to 450°C)

### Pressure Range

- Standard: 0 psig to 2700 psig (1 bar to 187 bar)
- Optional: 3480 psig (240 bar) maximum

### Materials

- Standard: Titanium
- Optional: Monel® or Hastelloy® alloys

### Process Connections

Flanged and compression fittings

### Mountings

Flowcell or cold tap

### Area Classifications

- Standard: General purpose
- Optional: Weatherproof Type 4X/IP66
- Optional: Explosion-proof enclosure Class I, Division 1, Groups B,C,&D
- Optional: Flameproof enclosure Class I, ⓂII 2 GD EEx d IIC T6

*Transducers and flowcells for specific applications are available. Consult GE for details.*

## Transducer Cables

- Standard: One pair of coaxial cables, type RG62 AU, or as specified for transducer type
- Optional: Lengths up to 1000 ft (330 m) maximum

## High-Temperature and High-Pressure Ultrasonic Flow Transducers

Bundle Waveguide Technology™ (BWT) System transducer and holder (see BWT System specifications) are available.



[www.gemeasurement.com](http://www.gemeasurement.com)

920-010E